



**Product:** <u>C5761</u> ☑

Teck90 1000V, 3+G C #10+12 Str BC, XLPE Ins M4, PVC Jkt, AIA Armor, Blk PVC Jkt, CSA HL SUN RES -40C

# **Product Description**

Teck90 1000V, 3+G Conductor 10+12AWG (7x18H) Bare Copper, XLPE Insulation M4 Color Code, PVC Inner Jacket, Aluminum Interlock Armor, Black PVC Outer Jacket, CSA HL SUN RES -40C

## **Technical Specifications**

## **Product Overview**

Suitable Applications:	CEC Power and Control Applications up to 600V

## **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	3	10 AWG	7x18	BC - Bare Copper
Ground Wire	1	12 AWG	7x20	BC - Bare Copper

## Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	XLP, XLPO, XLPE (Thermoset)	0.045 in (1.1 mm)	0.204 in mm	Black, Red, Blue
Ground Wire No Insulation				

### **Outer Shield**

Material No Shield

# Inner Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.063 in (1.6 mm)	0.565 in (14.4 mm)

### Armor

Armor Type & Material	Diameter Over Armor
AIA - Aluminum Interlock Armor	0.790 in (20.1 mm)

### **Outer Jacket**

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.048 in (1.2 mm)	0.886 in (22.5 mm)	Yes
Overall Cable Diameter (f	Nominal): 0.886 in	(22.5 mm)	

## **Electrical Characteristics**

### Electricals

Element	Nom. Conductor DCR	Max. Current
Conductor(s)	1.06 Ohm/1000ft	40 Amps per Conductor at 30°C
Ground Wire	1.68 Ohm/1000ft (5.51 Ohm/km)	

## Voltage

Voltage Rating

## **Mechanical Characteristics**

#### Temperature

Operating	Installation	
-40°C To +90°C	-25°C To +90°C	

#### Bend Radius

Stationary Min.	Installation Min.
7.08 in (180 mm)	7.08 in (180 mm)

Max. Pull Tension:	707.2 lbs (320.8 kg)
Bulk Cable Weight:	371 lbs/1000ft

## **Standards and Compliance**

Environmental Suitability: Indoor, Outdoor, Sunlight Resistance, UV Resistance, Burial	
CEC / C(UL) Compliance:	TECK 90, HL
European Directive Compliance: EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU	
APAC Compliance:	China RoHS II (GB/T 26572-2011)

## **History**

Update and Revision:	Revision Number: 0.176 Revision Date: 05-31-2024

## **Part Numbers**

#### Variants

Item #	Putup Type	UPC
C5761 01010000	Reel	612825284505
C5761 0102500	Reel	612825284529
C5761 0103280	Reel	
C5761 0105000	Reel	612825284543
C5761 0107500	Reel	612825284550
C5761 010984	Reel	612825284567
C5761 0109840	Reel	

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.